



GK309E

Ultra-slim GPS Tracker



GPS+WIFI+LBS positioning

Latest WIFI positioning enables the kids to be pinpointed accurately indoor



Auto-mute mode on classes

Never disturb the classes via auto-setting



IP65 dust and water proof

Prevent device breakdown from unexpectedly splashing by water



Voice monitor

Activate listen-in mode via text



SOS call & Speed-dial

Thumb sized button allowing urgent call during an emergency case



Geo-fence alarm

Create geofences in circle or rectangle for key locations



Ultra-long standby time

1200mAh battery allowing sufficient power supply & 6 days standby



Tracked by: SMS, APP, Web

Report location in real time through different interfaces

Application



Personal security



Employee



Luggage

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	64 Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-165dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤2sec Avg. cold start ≤35sec

Function & Package

Voice monitor range	≤5 meters
Button	3xSpeed dial, 1xSOS, 1xPower On/Off
Battery	1200mAh/3.7V lithium-polymer battery
Working voltage/current	3.7VDC/75mA
Charger voltage/current	5VDC/1000mA
Standby time	5-6 days (WIFI report every 10 min) 12 hours (GPS report every 30 sec)
Calling time	6 hours
Operating temperature	-20℃~ 60℃
Dimension	102.5(L)*62.0(W)*9.0(H)mm
Weight	70g

Contact

Jimi Electronic Co., Ltd
Shenzhen Concox Information Technology Co., Ltd

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.iconcox.com www.jimilab.com

Email: info@concox.cn info@jimilab.com